TREATMENT

SYSTEM DESCRIPTION (CONT.)

Table 2. Operating Parameters [10-17, 19, 20]

	Value								
	Subplot								
Parameter	A	В	С	D	E	F	G	н	Measurement Method
First Lift of Soil (a)					-				Wethou
Total Heterotrophs	6.4 × 10 ⁶ -	1.1 × 10 - 1 ⁷ .6 ×	7 ×10 ⁵ -	4.1 × 10 - 2 ⁶ .7 ×	1.5 × 10 - 7.78 ×	1.0 × 10 - 4.3 ×	1.9 × 10 ⁷ -	1.8 × 10 - 4 ⁷ .6 ×	
(cfu/gm)	7.4 × 10 ⁶	10 7	9.9 × 10 7	10 7	10 7	10 7	4.3 × 10 ⁷	10 7	(b)
PAH Degraders (cfu/gm)	1.0 ×10 ⁵ - 5.0 × 10 ⁷	3.0 × 10 -52.2 × 10 7	1.0 × 10 -55.7 × 10 6	2.0 × 10 - ⁵ 7.2 × 10 ⁶	2.8 × 10 - 1.9 × 10 7	1.4 × 10 - 5.7 × 10 6	3.6 ×10 ⁶ - 1.5 × 10 ⁷	3.2×10^{-6} - 3.0×10^{-7}	(c)
Mixing Rate/Frequency	Tilled once every 2 wks	Tilled once every 2 wks	Tilled once every 2 wks	Tilled once every 2 wks	Tilled once every 2 wks	Tilled once every 2 wks	Tilled once every 2 wks	Tilled once every 2 wks	
Moisture Content (%)	7.7 to 8.8	8.1 to 9.6	10.3 to 10.5	9.3 to 9.5	12.4 to 22.8	11.0 to 11.9	11.2 to 12.5	12.4 to 13.2	Not available
pH	6.8	6.8 to 7.2	7.0 to 7.7	6.6 to 7.2	6.7 to 6.8	6.8 to 7.1	6.4 to 6.8	6.5 to 6.7	USEPA Method SW-846/9045
Residence Time (months)	9	9	15	9	9	9	9	9	
Temperature (°F)	17 to 99	17 to 99	13 to 99	17 to 99	17 to 99	17 to 99	17 to 99	17 to 99	Thermometer (d)
Carbon/Total Kjeldahl Nitrogen	10.3	15.4	9 to 11.0	10.1	8.8	11.5	13.2	14.2	Not available
Hydrocarbon Degradation (mg/kg/mo)	58	18	13	38	28	20	38	38	Calculated value
Second Lift of Soil (a)	5	5		7	7	7	7	7	
Total Heterotrophs (cfu/gm)	6.3 × 10 - 6.6 × 10 ²	1.7 × 10 - 1.3 × 10 ³	N/A	1.8 × 10	1.3 × 10 - 7 8.4 × 10 6	1.2 × 10 - 2.5 × 10 ⁶	3.8 × 10	2.3 × 10	(b)
PAH Degraders (cfu/gm)	7.0 × 10 - 6 4.5 × 10	2.0 × 10 - 6.0 × 10	N/A	9.0 × 10	2.5 × 10 - ⁶ 6.2 × 10	3.1 × 10 - 1.7 × 10	4.2 × 10	5.5 × 10	(c)
Mixing Rate/Frequency	Tilled once every 2 wks	Tilled once every 2 wks	N/A	Tilled once every 2 wks	Tilled once every 2 wks	Tilled once every 2 wks	Tilled once every 2 wks	Tilled once every 2 wks	
Moisture Content (%)	10.3 to 15.4	12.0 to 11.6	N/A	12.4	12.9 to 21.1	14.5 to 19.0	14.8	12.9	Not available
pH	6.7 to 7.3	6.8 to 7.5	N/A	7.6	7.6	6.8 to 7.6	7.6	7.8	USEPA Method SW-845/9045
Residence Time (months)	10	10	N/A	6	6	6	6	6	
Temperature (°F)	13 to 102	13 to 102	N/A	13 to 94	13 to 94	13 to 94	13 to 94	13 to 94	Thermometer (d)
Carbon/Total Kieldahl									

TREATMENT

METSYS

DESCRIPTION (CONT.)

Table 2 (continued). Operating Parameters [10-17, 19, 20]

Value									
	Subplot								
Parameter	А	В	С	D	E	F	G	Н	Measurement Method
Third Lift of Soil (a)									
Total Heterotrophs (cfu/gm)	N/A	N/A	4.87 × 10 - 7.90 × 10	3.20 × 10 - 9.07 × 10	2.7 × 10 - 7.55 × 10	7.0 × 10 - 1.1 × 10	5.0 × 10 - 1.39 × 10	7.0 × 10 - 3.67 × 10	(b)
PAH Degraders (cfu/gm)	N/A	N/A	1.85 × 10 ⁴ 4.0 × 10 ⁵	1.15 × 10 ⁴ 3.0 × 10 ⁵	5.5 × 10 ⁻³ 4.0 × 10 ⁻⁵	2.75 × 10 ⁴ 3.0 × 10 ⁵	7.5 × 10 ⁻³ 4.90 × 10 ⁻⁶	2.95 × 10 ⁻⁴ 8.0 × 10 ⁻⁵	(c)
Mixing Rate/Frequency	N/A	N/A	Tilled once every 2 wks	Tilled once every 2 wks	Tilled once every 2 wks	Tilled once every 2 wks	Tilled once every 2 wks	Tilled once every 2 wks	
Moisture Content (%)	N/A	N/A	12.6 to 16.3	13.9 to 14.6	8.5 to 14.7	9.4 t 13.9	8.9 to 14.0	8.9 to 14.2	Not available
pH	N/A	N/A	6.4 to 7.0	6.5 to 6.8	6.6 to 6.9	6.7 to 6.9	6.7 to 7.0	6.7 to 7.0	USEPA Method SW-846/9045
Residence Time (months)	N/A	N/A	4	4	4	4	4	4	
Temperature (°F)	N/A	N/A	29 to 102	29 to 102	29 to 102	29 to 102	29 to 102	29 to 102	Thermometer (d)
Carbon/Total Kjeldahl Nitrogen	N/A	N/A	30 to 37	15 to 58	20 to 31	43 to 67	6 to 51	30 to 32	Not available

- N/A This lift of soil was not applied to this subplot.
- (a) The values for each lift of soil are ranges of values measured in samples collected from the time that the lift was applied to the subplot until the next lift of soil was applied to the subplot.
- (b) "Agar-Plate Method for Total Microbial Count," F. ClarkMethods of Soil Analysis Vol. 2, pp. 1460-1465.
- (c) "Replica Plating Method for Estimating Phenanthrene-Utilizing and Phenanthrene-Cometabolizing Microorganisms," Shiaris, M., Cooney, Applied and Environmental Microbiology, February 1983, Vol. 45, No. 2, pp. 706-710.
- (d) These values are for the ambient air temperatures measured between application of lifts.